
Stepan_®



Product Bulletin

Product Name

Chemical Structure



STEPANATE[®] SXS

Chemical Description

Sodium Xylenesulfonate

CAS Registry No.

1300-72-7 **INCI Name** Sodium Xylenesulfonate

Applications STEPANATE SXS is used in liquid detergent formulations as a solubilizer, coupling agent and cloud point depressant. The hydrotropic or solubilizing property of STEPANATE SXS allows materials to be incorporated in formulations that normally are incompatible. STEPANATE SXS is also useful in lowering the cloud point or crystallization temperature of complex blends. STEPANATE SXS contains no alcohol so it will not decrease the flash point of your formulation. It is also chemically inert in most formulations.

> STEPANATE SXS is commonly used as a coupling agent for surfactants in phosphate and silicate solutions. The coupling ability of STEPANATE SXS makes it possible to formulate detergents containing high percentages of inorganic builders. Heavy duty cleaners, wax strippers and complex dishwashing detergents can also be prepared without the use of organic solvents. It is also used as a non-caking agent in spray dried detergents.

Typical	Appearance at 25°C Clear liq	uid
Properties	pH. as is	9.0
	Actives, %	42
	Solids, % by Wt	44
	Crystallization Point, °C (°F) 16 (60)
	-9 (
	Freeze Point, °C (°F)	19)
	Cloud Point, °C (°F)	
	Color, Klett (as is)	ax.
	Viscosity at 0°C, cps	21
	Viscosity at 25 °C, cps	. 7
	Viscosity at 60 °C, cps	
	Flash Point (PMCC), °C (°F)	
	Density, g/ml (lbs/U.S. gal) 1.164 (9	
	RVOC, U.S. EPA, %	

Environmental Effects

Product is readily biodegradable. A detailed biodegradability statement is available upon request.

April 2024 Supersedes: January 2021 Page 1 of 2



® Health Effects	STEPANATE SXS is practically non-toxic orally (LD ₅₀ = 5 - 6 g/kg); it causes mild eye irritation and skin irritation. The product is also practically non-toxic to relatively harmless to aquatic organisms.				
Storage & Handling	Normal safety precautions (i.e., gloves and safety goggles) should be employed when handling STEPANATE SXS. Contact with the eyes and prolonged contact with the skin should be avoided. Wash thoroughly after handling material.				
	Standard Packaging: STEPANATE SXS is available in drums, totes and in bulk quantities.				
	and kept in a cool, dry place. Liquipa	k or HDPE plastic drums are recomr emperatures, it can crystallize and s	ATE SXS be stored in closed containers nended for storage of STEPANATE SXS. reparate. It should be heated slowly and		
	<u>Bulk Storage Recommendations</u> : STEPANATE SXS should be stored in 316 stainless steel or fiberglass with a corrosion liner. Mild agitation is recommended while storing to maintain homogeneity. Material should be stored between $23 - 40^{\circ}$ C ($75 - 105^{\circ}$ F). An internal hairpin coil of 316 stainless steel with low pressure steam (under 50 psig) should be used if heating is required. Pumps, pipes and transfer lines should be 316 stainless steel.				
Workplace Exposure	Occupational exposure can occur primarily through skin contact or via inhalation of vapors and mists. Engineering controls, personal protective equipment, and other workplace practices should be used to control these exposures.				
Clearances	The international inventories (country clearances) of STEPANATE SXS can be found in Section 15 of the Data Sheet (SDS). It is the responsibility of the formulator to review the chemical control regulations for country where the end product is intended to be sold or used. If you have any further questions regime inventories, please contact North America Technical Service at techserv@stepan.com.				
	STEPANATE SXS is available in Kosher grade.				
	STEPANATE SXS is approved in the United States for use under 40CFR 180.920.				
	STEPANATE SXS meets the U.S. EPA Safe Choice Program's surfactant screen and is listed on www.cleangredients.org (an on-line database for green formulators). For further information, visit <u>www.cleangredients.org</u> . Additional Stepan ingredient listings can be found at <u>www.stepan.com</u> .				
Product Stewardship	This product bulletin has been written in accordance with ACC's Product Stewardship guidelines.				
Additional Safety Information	A Safety Data Sheet (SDS) is availa	ble upon request.	Responsible Care		
	The information contained herein is based on the manufacturer's own study and the works of others and is subject to change without prior notice. The information is not intended to be all-inclusive, including as to the manner and conditions of use, handling, storage or disposal or other factors that may involve additional legal, environmental, safety or performance considerations. Nothing contained herein grants or extends a license, express or implied, in connection with any patents issued or pending of the manufacturer or others or shall be construed as a recommendation to infringe any patents or to violate any applicable laws. STEPAN COMPANY MAKES NO WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR USE, EXPRESS OR IMPLIED, AND NO OTHER WARRANTY OR GUARANTY, EXPRESS OR IMPLIED, IS MADE, INCLUDING AS TO INFORMATION REGARDING PERFORMANCE, SAFETY, SUITABILITY, STABILITY, ACCURACY, COMPLETENESS OR ADEQUACY. Stepan Company (and its employees, subsidiaries, and affiliates) shall not be liable (regardless of fault) to the vendee, its employees, or any other party for any direct, indirect, special or consequential damages arising out of or in connection with the information provided herein, including in respect of its accuracy, completeness, adequacy, furnishing, or use, or reliance upon such information. The vendee assumes and releases Stepan Company (and its employees, subsidiaries, and affiliates) from all liability, whether in tort, contract or otherwise to the fullest extent possible under the relevant law.				
April 2024 Supersedes: January 2021 Page 2 of 2	Stepan Corporate Headquarters Northbrook, Illinois 60062, U.S.A. Phone: 847-446-7500 Fax: 874-501-2100 Website: www.stepan.com	For Technical Service Call: Stepan North America +1-800-745-7837 Stepan Mexico +55-11-5089-2208 Stepan Quimica +55-11-5089-2200 Stepan Colombia +571-636-2808 Stepan Europe +33-476-505-160 Stepan Asia +656-879-9855 Stepan Philippines +656-879-9855	For Customer Service Call: Stepan North America +1-800-457-7673 Stepan Mexico +52-555-533-1967 Stepan Quimica +55-11-5089-2200 Stepan Colombia +57-6-8993125 Stepan UK +44-161-338-5511 Stepan France +33-476-50-51-00 Stepan Philippines +63-2-842-7951		

© 2024, Stepan Company. All rights reserved.